# Good. Safe. Yellow.

Klingspor Abrasive Screen

**AN 400** 





### **Grit sizes**

12	16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000
								<b>√</b>	✓	✓	✓	✓	✓	✓	V	✓	<b>√</b>	V	<b>√</b>	✓	✓				

### Structure

Grit	Aluminium oxide
Bonding	Resin
Backing	Polyester grid
Other	Waterproof, self-fastening
Delivery form	Discs, strips

# **Application**

Material	Paint/Varnish/Filler, gel coats, plaster, plasterboard walls, composite materials, wood, wood based materials
Application	Intermediate and finish grinding of paint/varnish/filler, composite materials and gel coats, grinding of filled joints and panels (dry construction), effective grinding of hard and soft wood materials
Machines	Orbital sander, long-neck sander, random orbital sander, angle grinder

# **Market segment**

Dry construction, painters and varnishers, woodworking industry, automotive and boat construction, windpower industry

## **Product utility**

Effective and full-surface dust extraction thanks to open grid structure, dust-free grinding extends the service life of the abrasive. At the same time, improved health and safety thanks to reduced dust formation at the work station. Independent of existing extraction hole patterns.