

Good. Safe. Yellow.

Abrasive sponge SW 512

Klingspor Schleifsysteme GmbH & Co. KG

Hüttenstraße 36 · 35708 Haiger · Germany

Fon +49 (0) 2773 922-0 · Fax +49 (0) 2773 922-186

sales@klingspor.de · www.klingspor.de





Properties

Grain	Silicon carbide
Coating	close
Available grits	120, 180, 220, 320
Other	Coated on one side, can be used wet and dry
Delivery forms	115 x 140 x 5

Applications

Material	<ul style="list-style-type: none">▶ Paint/Varnish/Filler▶ Wood▶ Plastic▶ Metals
Applications	hard-to-reach Areas such as indentations, profiles and edges, hard-to-machine materials

Market segment

Artisans, repair shops, joineries

Advantages

Thin, Ultra flexible sanding sponge for particularly hard-to-reach areas such as indentations, profiles and edges. Tight foam structure, allowing for exceptionally uniform pressure distribution and an extra fine finish.

No bending and creases. Sharp-edged silicon Carbide for increased aggressiveness and processing of hard-to-machine materials.

Width x Length x Height in mm	Grit	Packing unit/pcs.	Cat.
115 x 140 x 5	120	100	337850
115 x 140 x 5	180	100	337851
115 x 140 x 5	220	100	337852
115 x 140 x 5	320	100	337853